

Plinx



Features

- Specially designed for suspended installation, easy installation kit
- Easily connectable
- Full aluminum extrusion body, rigid, robust, durable
- Modern, stylish
- Durable with life span over 50,000 hours
- 5 Years Guarantee
- Simple and convenient installation

Applications

A perfect luminaire for open space area in various applications such as:

- Super Markets
- Offices
- Workshops
- Shops
- Schools
- Hospitals
- Meeting Rooms
-



REV 0.9
07/25/2014

Sheenly LED Linear Light

Sheenly's new designed LED Linear Light Plinx comes with complete aluminum extrusion body, making it perfect for suspension and easy for multiple linear connections.

Plinx is the ideal replacement for traditional grid lights and fluorescent tubes. It is powered by low voltage constant current driver, which is safety, energy saving and long life.

Specifications

Dimension

26W	900*150*10 mm
40W	1200*150*10 mm
50W	1450*150*10 mm

Power & Lumen Output

26W	2000 lm @ 4000K
40W	3000 lm @ 4000K
50W	4000 lm @ 4000K

Color Temperature

Warm White	3000K-3300K
Natural White	4000K-4300K
Pure White	5700K-6000K

Color Rendering Index

>80

Rated Life (L70)

50,000 Hours

Housing

Aluminum Opal

Beam Spread

120°

Operating Temperature

-20°C to +60°C (Amb.)

Input Voltage

200-240V/AC

Power Factor

>0.95

Working Voltage

26W	34V/DC
40W	25V/DC
50W	34V/DC

Working Current

26W	700 mA
40W	1400 mA
50W	1400 mA

Net Weight

2.9 Kg

Glow Wire

650 °C (850°C Optional)

IP

IP20



IK

IK08

Installation

Suspension
Surface Mounted

Dimension and Illumination Diagram



Ordering Information

Sheenly	Class	Watt	CCT	Model	Finishing	Options
SL=Sheenly Lighting	PAN=Panel	26W 40W 50W	WW=3000K NW=4000K PW=6000K	PX	SI=Silver	

Part Number	Power	CCT	Lumen Output	Beam	Dimension
SL-PAN-26W-WW-PX90	20W	3000K	1800	120°	900*150*10 mm
SL-PAN-26W-NW-PX90	20W	4000K	2000	120°	900*150*10 mm
SL-PAN-26W-PW-PX90	20W	6000K	2200	120°	900*150*10 mm
SL-PAN-40W-WW-PX120	40W	3000K	2800	120°	1200*150*10 mm
SL-PAN-40W-NW-PX120	40W	4000K	3000	120°	1200*150*10 mm
SL-PAN-40W-PW-PX120	40W	6000K	3200	120°	1200*150*10 mm
SL-PAN-50W-WW-PX150	50W	3000K	3800	120°	1450*150*10 mm
SL-PAN-50W-NW-PX150	50W	4000K	4000	120°	1450*150*10 mm
SL-PAN-50W-PW-PX150	50W	6000K	4200	120°	1450*150*10 mm

Accessory



Suspension Kit:
Driver Box ,Steel Cables, Screws, accessories, etc.

Shanghai Sheenly Lighting Co., Ltd.










No. 2755 SanLu Road, Minhang District Shanghai 201112, China

Tel: (+86)-21-6411 3138 Fax: (+86)-21-6411 3862

*All specifications subject to change without notice.

©2009-2014 Sheenly Lighting all rights reserved.

Plinx Suspension Installation Manual



**Lighting Up
a New World**